

Tender text: Ampatop Seal Weldable roof membrane

Position	Specifications			
1	General Carrying out Ampatop Seal in connection with Ampacoll system sealing technology as roof membrane according to country-specific standards			
	Technical Specifications: Roll dimensions: sD value: Weight: Fire index: Fire performance: CE marking:	1.5 m x 30 m / 3.0 m x 20 m / 1.5 0.20 m 350 g/m2 4.2, VKF E, EN 13501-1 EN13859-1:2014	m x 400 m / 3.0 m x 400 m	
2	Delivery and laying of the weldable roof membrane Ampatop Seal on pressure-proof, clean, and level surfaces parallel to the eaves or the rafters. In case of roof pitch between 5° and 10°m use boarding or wood boards to prevent water pockets.			
	Build all joints with 10 cm overlaps, fasten concealed with clamps or clout nails in the overlap area.			
	Seal all overlaps either with Ampacoll LiquiSeal or with hot air. Carry out diagonal joints the same way.			
	Bottom membrane laid on intake sheet, top membrane pulled over roofridge.			
	Seal nail and screw locations of the counter battens with Ampacoll ND or Ampacoll ND tape. Use Ampacoll ND Duo for roof pitch below 25° DN.			
	Roof pitch: (minimum pitch 5°)			
	Roof shape:			
	Quantitym ²	Unit price	Total price	
3	Sealing work (surcharges to item 2)			
3.1	Installation of boards Boards on breakthroughs such as chimneys, skylights, and other installations have to be carried out with membrane strips, at least 15 cm high, and sealed with Ampacoll LiquiSeal or hot air.			
	Quantityrunning price	g metre	Unit price Total	

3.2	Edge connections Connections to intake sheets are to be carried out with double-sided adhesive tape Ampatop DoubleSeal in double layers next to each other. Please note the installation instructions regarding connections that keep their volume.			
	Quantityrunning metre Unit price Total price			
3.3	UV-proof installation of roof membrane eaves connection (with perforated sheeting above the gutter) using Ampatop SealEdge eaves flashing.			
3.4	Circular breakthroughs There are two options to make breakthroughs rain-proof and water-proof: using the prefabricated leathering Ampacoll TubeSeal or the manual construction with base plate (tableau) and vent pipe sleeve.			
3.4.1	Circular breakthroughs with diameters of 80 – 120 mm for roofs with a pitch from 5° to max. 25° DN. Delivery and installation of leathering Ampacoll TubeSeal.			
	QuantityPiece Unit price Total price			
3.4.2	Circular breakthroughs with unwinding of up to 50 cm Construction and installation of a base plate (tableau) and a vent pipe sleeve, at least 15 cm high and sealed with Ampacoll LiquiSeal or hot air, with each other and with the underlayment Ampatop Seal.			
	QuantityPiece Unit price Total price			
3.4.3	Circular breakthroughs with unwinding > 50 cm to 100 cm Construction and installation of a base plate (tableau) and a vent pipe sleeve, at least 15 cm high and sealed with Ampacoll LiquiSeal or hot air, with each other and with the underlayment Ampatop Seal.			
	QuantityPiece Unit price Total price			
3.4.4	Circular breakthroughs with unwinding > 100 cm to 200 cm (Openings with unwinding of more than 200 cm are considered installations of boards and are listed there.)			
	Construction and installation of a base plate (tableau) and a vent pipe sleeve, at least 15 cm high and sealed with Ampacoll LiquiSeal or hot air, with each other and with the underlayment Ampatop Seal.			
	QuantityPiece Unit price Total price			

- 4 Installation of boards and pipe collars
- 4.1 Connect installation of boards and pipe collars as defined in items 3.1 and 3.3 with adhesive tape Ampacoll XT or the double-sided adhesive tape Ampatop DoubleSeal to the rising parts (walls, pipes, and window frames) rain-proof.

 Quantity.....running metre
 Unit price.....
 Total

 price.....
 Total

- 5 Priming the surface (surcharge to item 1).
- 5.1 Cleaning the surface of dirt and coarse contamination.
- 5.1 Smoothing sharp-edged high spots in case of scaled boarding or slabs.
- 5.3 Laying of pressure-proof base or separating layer in case of shingle underlayments (renovations).

6 Supplier and documentation All product data as well as the handling instructions can be obtained from the technical documentation of the Ampack company.

> Additional information and suppliers: Ampack AG Seebleichestrasse 50 9401 Rorschach, Switzerland Tel. +41 (0)71 858 38 00 Fax +41 (0)71 858 38 37 E-mail: ampack@ampack.ch www.ampack.ch

Note

Content considerations

Adjustments by the user will remain necessary on occasion. Texts for tender proposals describe standard situations only. Special cases must be considered separately. When carrying out the creation, Ampack AG is guided by the best available technology, the recognised rules of the building trade, association requirements and current standards and regulations. In the event of doubt, the details in the documentation or in the brochures and flyers of Ampack AG apply.

Legal considerations

The preparation of texts for invitations to tender is a voluntary, non-payable additional service of Ampack, and is intended as an aid for architects, planners and processors. It is carried out to the best of the company's knowledge, but expressly excludes any liability derived from consulting services. See the General Terms & Conditions of Ampack AG for further information.

Permission for use by customers of Ampack AG

The texts for invitations to tender can be used by our customers (architects, planners and processor) for their own purposes. Any disclosure or publication in printed matter or electronic media is not permitted. Constructive criticism and amendments are expressly requested and welcomed by the author. To facilitate the transfer to tender proposals, unnecessary formatting has been omitted.

Ampack AG Ulrich Höing Head Technology and Development Seebleichestrasse 50 CH-9400 Rorschach +41 71 858 38 00 Tel +41 71 858 38 37 Fax ulrich@ampack.ch

Copyright Ampack AG, CH-9400 Rorschach

Last updated: 28.09.2018